

CS-C3232 Specifications

basic specifications:

Configuration:	Workgroup Color Multifunctional with Standard Network Print / Scan and Optional Fax / Network Fax. Standard Duplex, 500 x 2 Sheet Paper Drawer and 100 Sheet Multipurpose Tray, Standard 40GB System Hard Disk Drive, Optional Document Processor, Paper Handling and Advanced Finishing .
Resolution:	Multi Bit 600 x 600 DPI Resolution / 256 Levels
System Memory:	Standard 768MB RAM; 40GB HDD
Magnification:	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, Plus 25-400% Zoom
Electrical Requirements:	120V, 60Hz, T2A
Dimensions:	23.82"W x 25.98"D x 29.33"H
Weight:	216 lbs
Max Monthly Volume:	125,000 Pages Per Month

output speeds:

Warm-Up Time:	Within 45 Seconds, Program During Warmup, Auto Start
First Copy Out (Color / Mono):	7.9/5.9 Seconds
First Print Out (Color / Mono):	7.9/5.9 Seconds
Pages Per Minute (Color / Mono):	32/32 Letter, 16/16 Legal and Ledger

paper supply:

Standard Paper Sources:	Dual 500 Sheet Drawers, 100 Sheet MPT, Auto Selection / Switching, Add Paper While Running
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size :	5.5" x 8.5" - 11" x 17"
Std / Max Paper Capacity:	1,100 / 4,100
Paper Weight:	16 - 28 lb Bond via Paper Drawers, 16 lb Bond -120 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Cardstock, Envelopes

duplex unit:

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

copy functions:

Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO, Map, Up to 999, Auto Reset to 1
Continuous Copy:	
Additional Features:	Positive / Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Rotate Sort, Full-Color & Monochrome copy sets in same run, Electronic Sort, Margin Shift, Dual Access, Signature Booklet Making, XY-Zoom, Job Management: Job Interrupt, Job Build, 8 Job Programs, Repeat Copy, 1,000 Department Management Codes. Color Adjustment: OneTouch, Color Balance -11 levels, Hue, Auto Exposure - 7 or 13 levels, 6 Monotone Colors, Manual Exposure - 7 or 13 levels, Auto GrayScale, Sharpness - 6 levels, Color Calibration

paper handling options:

document processor: DP-710

Type:	Reversing Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size Originals
Capacity:	100 Sheet RADF / 32 Letter Size Originals Per Minute
Paper Weight:	9 - 42 lb Bond
Dimensions / Weight:	22.5"W x 19.2"D x 5.28"H / 25.4 lbs

finisher: DF-710

Stack Capacity:	Main Tray: 3,000 Sheets; Sub Tray (B): 50 Sheets; Sub Tray (C): 200 Sheets
Paper Size:	Main: 8.5" x 11" - 11" x 17"; Sub Tray (B) : 5.5" x 8.5" - 11" x 17" Sub Tray (C): 8.5" x 11"
Paper Weight:	16 - 28 lb Bond
Staple Capacity:	50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	4 Positions: Top Left, Bottom Left, Left/Top Side, Center Bind
Punch:	Optional 2 and 3 Hole
Dimensions / Weight:	26.9"W x 22.2"D x 42.8"H / 110 lbs

simple finisher: DF-730

Stack Capacity:	Main Tray: 1,000 Sheets
Paper Size:	Main: 8.5" x 11" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	1 Positions: Top Left
Dimensions / Weight:	21.9"W x 20.7"D x 36.0"H / 55 lbs

booklet folder unit: BF-710

Folding Capacity:	Up to 16 Sheets
Capacity:	1 - 3 Sheets - 30 Booklets; 4 - 6 Sheets - 20 Booklets; 7 - 16 Sheets - 10 Booklets
Paper Size:	8.5" x 11", 11" x 17", 8.5" x 14"
Paper Weight:	16 - 28 lb Bond, Over 20 lb is one sheet only
Dimensions / Weight:	25.9"W x 17.9"D x 10.5"H / 53 lbs

job separator: JS-710

Stack Capacity:	100 Sheets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 lb - 28 lb Bond

multi-bin mailbox: MT-710

Number of Trays:	7
Tray Capacity:	100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"
Paper Weight:	16 - 20 lb Bond
Dimensions / Weight:	20.0"W x 15.7"D x 18.5"H / 22 lbs

punch unit: PH-5A

Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Number of Holes:	2 and 3
Weight:	6.6 lbs

large capacity tray: PF-750

Paper Capacity:	3,000 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11"
Dimensions / Weight:	23.0"W x 23.6"D x 12.4"H/ 48 lbs

dual paper drawers: PF-700

Paper Capacity:	500 x 2 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	5.5" x 8.5" - 11" x 17"
Dimensions / Weight:	23.0"W x 23.2"D x 12.4"H/ 57.3 lbs

connectivity:

standard print/scan:

PRINT:	
Controller:	Embedded PowerPC750GL / 800 MHz Controller
Printer Memory:	Standard 256MB, Upgradeable to 1-GB via 100 Pin DIMMS, Optional e-MPS Printer HDD, Standard CF Card Slot (Type 1) PRESCRIBE, PCL6 (PCL XL, PCL 5c), KPDL3 (P53), KGL (HP-GL/2)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5c), KPDL3 (P53), KGL (HP-GL/2)
Fonts:	80 Outline Fonts for PCL XL/5c, 136 Outline Fonts for KPDL3, 1 Bitmap Font
Windows™ OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP/2003
Novell™ OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/10.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	10/100BaseTX, Parallel IEEE1284, High Speed USB 2.0
KUIO LV Expansion Slots (2):	Optional e-MPS Printer Hard Disk Drive Optional IB-20 10/100BaseTX, 10Base2; IB-11 Serial Interface
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows 64-Bit Drivers
Utilities:	KM-NET Viewer, PDF Direct Print, KM-NET for Client, KM-NET Printer Disk Manager, PRESCRIBE Utilities, KX Spool Center, Kyocera Command Center, KM Net for Accounting

scan:

Type:	Color and Monochrome Scanner
Resolution:	200, 300, 400, 600 DPI
Scan Speed (Color / Mono):	Up to 32 / 32 Sheets Per Minute
File Formats (Color / Mono):	PDF, JPEG / PDE, TIFF
Connectivity:	Standard 10/100BaseTX
Supported Protocols:	TCP/IP
Scanning Features:	KM Document Flow (Scan to Database) TWAIN (PC/Mac) Scan to File (PC/Mac), Scan to FTP, Scan to E-Mail (LDAP compatible)
Driver:	TWAIN Driver
Utilities:	KM DB-Assistant, KM Scanner File Utility, KM Scanner Address Book, Address Book Editor, LDAP Converter Utility, Network Advanced Setup Utilities, Scan to Mac Utility

optional printer hard disk drive: HD-5

Enables Document Printing and e-MPS Functions; Private Print, Job Storage, Quick Copy, Proof & Hold, Virtual MailBoxes

optional data security kit: (D)

Provides Security Overwrite and Encryption for Print, Copy, and Scan

optional fax/network fax: FAX SYSTEM (N)

Compatibility:	Super G3
Transmission Speed:	Approximately 3 Seconds per page
Modem Speed:	33.6 Kbps with Auto Fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory:	Std MB /Max 32MB
Driver:	KM Network Fax Driver
Utilities:	Address Book for Network Fax, Address Editor for Fax
Additional Features:	Duplex TX/RX, Confidential RX/TX, Polling, Broadcasting, 2 in 1 RX

optional PDF enhancement kit: (UG-31)

PDF Encryption; PDF Compression

additional options:

KYOcapture, iTag, 32MB Fax Memory Board (MM13-32), Platen Cover (D), Attachment Kit (AK-710), Stand



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2006 Kyocera Mita America, Inc.
www.copystar.com

